


Slope Tops



Slope tops are frequently preferred over flat tops to prevent the buildup of dust and debris and deter using locker tops for storage. Three variations of slope construction are available: Unit slope tops, Slope hoods and Slope top kits (Stock converter for Knock Down Series).




UNIT SLOPE TOPS

Unit Slope Tops cover the width of one locker frame only. Lockers with Unit Slope Tops have sides with mitered top ends with a rise equal to 1/3 of the locker depth, plus longer backs that meet the rear edge of the slope top, Unit Slope Tops are used in place of the standard flat tops. (Not for use on Heavy Duty Series, Open Front Series or All Welded Series.)

Unit Slop Tops are available in the following width and depth:

 $9x12,\ 9x15,\ 9x18,\ 12x12,\ 12x15,\ 12x18,\ 12x21,\ 15x12,\ 15x15,\ 15x18,\ 15x21,\ 18x18,\ 18x21,\ 18x24,\ 24x18,\ 24x21\ and\ 24x24.$

Slope Top Kits are available in the following width, depth and height:



Continuous Slope Hoods fit on top of flat top lockers. They can be used on new lockers, or on a retrofit basis. All hoods are furnished in 72" lengths and must be cut to length during installation. Intermediate splices, ends and rear supports (2 per hood) complete the installation, and must be ordered separately.

Slope Hoods are available in the following width, depths and heights: 72x12x5, 72x15x6, 72x18x7, 72x21x8, and 72x24x9.

Slope Ends and Hood Splice available in the following depths and heights: 12x5, 15x6, 18x7, 21x8 and 24x9.

